

HG "satin gloss polish"

HELPS PREVENTS STAINS AND STUBBORN DIRT. ENHANCES THE COLOUR AND TEXTURE. SELF-SHINING WITH SATIN GLOSS. A NON SLIPPERY FINISH.

- APPLICATION

For unglazed quarry tiles, floor tiles and slate.

- DIRECTIONS FOR USE

Prior to applying HG "satin gloss polish" (HG "golvpolish") the floor should be thoroughly cleaned, preferably with HG "cement grout film remover" (HG "remover") to clean off grease, old layers of wax etc. After wet cleaning the floor should be left to dry thoroughly for 3 days. With floor heating 24 hours. Turn off your floor heating 12 hours before treatment. On porous surfaces such as slate, brick or flagstones first use HG "impregnating sealer" (HG "impregnator"). To avoid foam, do not stir or shake the bottle before use. The HG "satin gloss polish" (HG "golvpolish") should be applied with a fluff-free cloth, e.g. a used tea cloth wrapped around a squeegee, or, on rough surfaces, use a velvet paint roller suitable for acrylic paint. Pour some HG "satin gloss polish" (HG "golvpolish") on the cloth and always spread the polish in one direction. Do not rub or buff. Once the HG "satin gloss polish" (HG "golvpolish") has dried after approx. 40 mins. A second coat should be applied at right angles. Dries after 3 hours, but allow 3 days for the HG "satin gloss polish" (HG "golvpolish") to become fully water resistant.

Maintenance: With HG "shine cleaner" (HG "superfloor"). To strip off old coats of HG "satin gloss polish" (HG "golvpolish") annually use HG "polish, wax and dirt remover" (HG "remover").

- PRODUCT INFORMATION

Properties	:	self shining wax, metal bond, sustained versus black heel strips, water resistant. Contains no silicones.
S.G.	:	± 1,02 g/ml
pH	:	± 9
Usage	:	40 m ² per ltr per layer
Active matter	:	± 13%
Components	:	acrylic polymers, polyethylene emulsion, ammonia resin solution, weak makers and flowing medium, preserving agent.

- PACKAGING
 - : 6 x 1 ltr
 - 6 x 2 ltr
 - 1 x 25 ltr

- **PRECAUTIONS**

Newly laid floors; allow moisture to evaporate thoroughly and allow to dry, prior to applying HG “satin gloss polish” (HG “golvpolish”). For interior use only

S2- Keep out of the reach of children. **S46-** If swallowed, seek medical advice immediately and show this container or label. For calcareous natural stone: see our marble range. For terra cotta tiles see our cotto range. Keep in a frost-free area..