

# HG "remover"

INTENSIVE (DEEP) CLEANING.  
REMOVES POLISH, WAX, GREASE, STUBBORN DIRT AND OILS.  
SELF ACTIVE.

- APPLICATION

For quarry tiles and non calcareous natural stone.

- DIRECTIONS FOR USE

For difficult areas dilute HG "remover" with a minimum 1:4 parts of lukewarm water. In less severe cases dilute 1:10 parts of lukewarm water. When a scrubbing machine is used dilute 1:50 up to 1:100, depending on the degree of dirt. Apply the solution liberally on the floor treating up to 10-15m<sup>2</sup> at a time. Leave the solution to work for approx. 5-10 minutes. Do not allow the floor to dry out. Scrub the floor and when clean, mop up the emulsified dirt. Rinse 2 or 3 times thoroughly with clean water afterwards.

- PRODUCT INFORMATION

Characteristics	: low foaming, highly concentrated cleaning agent
S.G.	: 1.03 g/ml
pH	: 13
Usage	: 20-40 m <sup>2</sup> /L (100-250 m <sup>2</sup> /L in case where a scrubbing machine is used)
Active matter	: 41%
Components	: nonionics, NTA, sequestering agents, alkalines, solvents and water

- PACKAGING

: 6 x 1.0 L  
4 x 5.0 L  
1 x 25.0 L

- PRECAUTIONS

**R36**- Irritating to eyes. **S2**- Keep out of the reach of children. **S25**- Avoid contact with eyes. **S26**- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. **S46**- If swallowed, seek medical advice immediately and show this container or label. **S64**- If swallowed, rinse mouth with water (only if the person is conscious). For marble and other calcareous natural stone please see our special marble products.