

HG "super protector for wall and floor grout"

PROVIDES COMPLETELY COLOURLESS, INVISIBLE PROTECTION WHICH ADHERES TO CEMENT GROUT. GIVES OUTSTANDING PROTECTION AGAINST THE PENETRATION OF (COOKING) OIL, FAT AND HUMIDITY, IN PARTICULAR. IN ADDITION, IT ALSO PROTECTS THE GROUT AGAINST MOULD FORMATION, SCALE AND OTHER FORMS OF CONTAMINATION.

- APPLICATION

On cement grout joints between floor tiles or wall tiles.

- DIRECTIONS FOR USE

Before applying, the grout must be both completely clean and dry. Therefore first clean all grouting thoroughly with HG "grout cleaner" or in bathrooms etc. with HG "hagesan blue". Rinse the joints well with clean water and leave to dry for 24 hours. Let new grout set and dry completely.

Floor grout in bathrooms and kitchens etc:

Apply HG "super protector for wall and floor grout" with the enclosed pipette. Use 1-2 ml liquid per running meter of the joint (of 0,5 cm width).

Wall grout bathrooms and kitchens etc:

Apply HG "super protector for wall and floor grout" to the grout joints using a brush until saturated and leave to dry for 1 hour. A second treatment is recommended to obtain optimum protection. Any excess on the grout or adjoining tile edges can easily be removed by using a cloth. The surface can be cleaned as usual after 36 – 48 hours. Allow approximately 3 hours after treatment before walking on floors. However, wait 8 hours before using floors treated in bathrooms and showers

- PRODUCT INFORMATION

Characteristics	: transparent, colourless liquid
Density	: 0,99 g/ml
Usage	: 250 ml per 30 – 40 m ² of tiled surface area (based on tiles of 30 x 30 cm with grout joints 0,5 cm width)
Components	: fluorsurfactant, kationics, water

- PACKAGING : 6 x 250 ml

- PRECAUTIONS

Turn off under floor heating, before applying HG "super protector for wall and floor grout". Keep in a frost-free area. **S2**- Keep out of the reach of children. **S46**-If swallowed, seek medical advice immediately and show this container or label.