



**tilemaster
adhesives**

20 x 1mtr. Roll

Anti-fracture Mat

Anti-fracture / Uncoupling Matting for Floors Subject to Limited Movement

- Three layer anti-fracture / uncoupling mat designed to accommodate & absorb lateral movement in sub-floors
- Genuine fast-track system – can be tiled over immediately after fitting the mat
- Only 0.85mm thick - minimises height build-up
- Ideal for plywood / chipboard overlay and T & G floorboards
- Ideal for underfloor heating systems
- Use below ceramic, porcelain & natural stone tiles
- Easy to install – simply cut & place




**tilemaster
adhesives**

Tilemaster Adhesives Ltd.,
Unit 4 Tomlinson Point, Tomlinson Road,
Leyland, Lancashire, PR25 2DY.
Tel: +44 (0) 845 208 0040 / 01772 456831
Fax: +44 (0) 845 208 0041
email: info@tilemasteradhesives.co.uk

Tilemaster Anti-fracture Mat Installation Guide

- 1 Make sure the original substrate is firm, stable and in good condition
- 2 Ensure the surface is dry and free of any contaminants, loose dust or dirt
- 3 Prime the substrate where necessary with Primeplus diluted accordingly for the relevant surface as instructed on the Primeplus packaging
- 4 Apply a thin 2 - 3mm bed of adhesive and lay the anti-fracture mat while the adhesive is still moist ensuring a uniformed and solid layer of adhesive between substrate and matting
- 5 Simply butt-joint the matting. Overlapping or the use of jointing tape is not required
- 6 Tiling can commence immediately after laying the Tilemaster Anti-fracture Mat using one of several Tilemaster adhesives as listed in item D below



A Solid Substrate or
Timber Substrate

B Rapid Setaflex
Trade FlexiRapid
Ultimate

C Tilemaster
Anti-fracture Mat

D Rapid Setaflex
Trade FlexiRapid
Ultimate

*The equivalent Standard
Setting adhesive is
also suitable*

E Grout 3000
Flexigrout

www.tilemasteradhesives.co.uk